



RecuBox ELITE

ISOTHERMAL / REFRIGERATED



GENERAL INFORMATION

PANELS

Components	Thickness
Roof	75 mm
Sidewalls	75 mm
Frontwall	75 mm
Rear doors	75 mm
Platform/Floor	110 mm

Our isothermal box body Recubox ELITE is designed for the transport of perishable and frozen food in **medium and long distance**. It is a box body for vehicles with total maximum weight (GVWR) of up to 12 tons.

Recubox ELITE has a system of assembly of **double profiling (interior / exterior)** that offers an additional resistance, compared with units of the same segment. It stands out for its **platform of high resistance**, composed of reinforcements that, by their arrangement, composition and weight reduction, confer to the platform the consistency necessary **for a daily work under very demanding conditions**.

STANDAR SPECIFICATION

- External and internal profiles of high strength aluminum powder-coated (RAL 9016)
- Internal kick-plate reinforced with "L" aluminum base, bolted to the floor to ensure durability
- Stainless steel rear frame
- Rear doors with EPDM rubber contour with 5 lips.
- 2 Rear doors with EPDM rubber perimeter with 5 lips
- Stainless steel locks and hinges
- Interior LED light with motion detection
- Front and rear LED position lights
- Third brake light
- Protection rear bumpers
- Protection conic rubbers on rear doors
- Anti-slip polyester floor
- 2 Drains for water evacuation
- Galvanized steel or powder coated steel subframe.

ADDITIONAL ACCESSORIES

- Backside with 1 or 3 doors.
- Channeling for second evaporator.
- Galvanized, aluminum or stainless steel lashing rails
- Fixed, mobile or soft separating panel
- Single or double side door.
- Extension of the rear frame for the entrance of forklifts
- Nose in rear frame for mounting of tail lift
- Tools box
- Mudguards
- Retractable stairs